Certificate of Compliance

No. 2P160229.MFP0C12



Certificate's Holder:

Moulded Fibreglass Products Corporate Office: 3rd Floor, 65 Cotton Street,

Kolkata – 700 007, West Bengal, India

Works: Gangarampur Road, Banerjeepara, Maheshtala, Kolkata – 700 141, West Bengal, India.

Certification ECM Mark:

(R) Type **Approved**

Product: Model(s):

Nylon Cable Ties (see the following annex I)

Verification to: Standard:

EN 62275:2015

related to CE Directive(s): 2014/35/EU (Low Voltage)

2011/65/EC (Restriction of Hazardous Substances)

Remark: The product(s) has been verified on a voluntary basis. The product(s) satisfies the requirements of the Certification Mark of ECM, in reference to the above listed Standard(s). The above Certification Mark can be affixed on the product(s) accordingly to the ECM regulation about its release and its use. Regulation can be found at www.entecerma.it.

Whereas the Manufacturer is responsible of the CE certification of the product(s) and not exempted to perform all the necessary activities before placing the product(s) on the market.

The Manufacturer is also responsible to maintain efficient the internal production control to ensure the product(s) are in compliance with the Certification ECM Mark.

This certificate can be checked for validity at www.entecerma.it

Date of issue 24 February 2016



Expiry date 23 February 2021



Annex I

No. 2P160229.MFP0C12



Model(s):

| Sr. No. | Products | Models |
|---------|------------------|--------------------------|
| | | Miniature Series: |
| 1 | Nylon Cable Ties | Length – 100 to 300 mm |
| | | Width – 1.8 to 2.7 mm |
| | | Thickness – 1.0 mm |
| | | Intermediate Series: |
| | 5.37(4) | Length – 150 to 350 mm |
| | | Width – 3.0 to 3.7 mm |
| | | Thickness – 1.2 mm |
| | | Standard Series: |
| | | Length – 200 to 500 mm |
| | 7/ 10 | Width – 4.0 to 4.8 mm |
| | | Thickness – 1.3 mm |
| | / = | Heavy Duty Series: |
| | | Length – 150 to 750 mm |
| | | Width – 7.6 mm |
| | | Thickness – 1.6 mm |
| | | Extra Heavy Duty Series: |
| | | Length – 460 to 1230 mm |
| | | Width – 8.8 to 9.0 mm |
| | | Thickness – 1.8 mm |